

FAST M1k



HIGH-SPEED VGA-FORMAT SCIENTIFIC THERMAL IMAGING

KEY FEATURES



ULTRAHIGH FRAME RATE



HIGH-SPEED INTERNAL MEMORY



HIGH SENSITIVITY




ADVANCED CALIBRATION


The FAST-IR series includes the fastest infrared cameras available on the market. The FAST M1k features a high sensitivity 640 x 512 pixel InSb array detector capable of acquiring full frame images at up to 1012 frames per second. This combination of temporal resolution and large format imagery deliver a high end capability to monitor fast thermal events over a wide field of view.



FAST M1k



Fireworks In-house Testing



Pulsed Detonation Rocket Engine

SPECIFICATIONS

Detector Type	Cooled InSb
Detector Format	640 x 512 pixels
Spectral Range	1.5 – 5.4 µm
Detector Pitch	25 μm
Aperture Size	F/2.5
Typical NETD	25 mK
Exposure Time	0.27 µs to full frame rate
Frame Rate	1 012 Hz
Maximum Frame Rate	11 000 Hz @ 64 × 64 40 000 Hz @ 64 × 8
Environmental Resistance	IP67
Operational Temperature	-15 °C to +50 °C
Storage Temperature	-35 °C to $+60$ °C
Lens Mount	Bayonet









