## **IMAGE INTENSIFIER TUBE**







PHOTONIS IS THE LEADER IN DESIGN AND MANUFACTURING OF STATE-OF-THE-ART IMAGE INTENSIFIER TUBES FOR MILITARY AND COMMERCIAL APPLICATIONS

The XR5 Image Intensifier Tube (IIT) represents the technological standard for night vision and is available in a variety of inverting and non-inverting formats for existing and new optical systems.

A prominent feature on the XR5 is the integrated Auto-Gated power supply, facilitating operations under dynamic lighting conditions. The XR5 IIT can suit a variety of environments, under low light levels.



\*Detection, Recognition, Identification

### **TECHNICAL SPECIFICATIONS**

	MINIMUM	TYPICAL	MAXIMUM	UNIT
FOM (Figure Of Merit) - 18mm (P43)	1472	1600	•	•
Signal-to-Noise Ratio	23	25	•	•
Limiting resolution	64	68	•	lp/mm

#### **FAST AUTO-GATING DATA**

High Light Level resolution (2001x)	55	•	•	lp/mm
Response time	•	0,2	0,4	S
Rise time Off-to-On	•	0,7	0,9	S
Input current	•	25	30	mA

#### **OTHER TECHNICAL DATA**

Phosphor	P43 - green (also available in P45 - white)			
Operational life time	10.000	•	•	hours
Halo (with 0,35mm input spot)	•	0,85	•	mm
Gain at 2 x 10 <sup>-5</sup> lx	10.000	•	20.000	cd/m²/lx
(Gain at 2 x 10 <sup>-6</sup> fc)	(31.000)	•	(63.000)	fL/fc
Max. Output Brightness (MOB)	4	•	17	cd/m²
(Max. Output Brightness)	(1,2)	•	(4,9)	fL
Equivalent Brightness Illumination (E.B.I)	•	0,15	0,25	μlx
Weight (18mm ANVIS)	•	70	75	g
Shock resistance	500	•	•	g's

# Photonis, worldwide night vision

11111111111111111111



**ITAR FREE** 

expert for more than 85 years



PHOTONIS LEGACY IMAGE INTENSIFIER TUBE



**MADE IN EU** 



NV SALES REPRESENTATIVES ALL OVER THE WORLD









